

# AUTO-SHUT-OFF SCREWDRIVER

## RRI-SL21104

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

### Characteristics:

- \* New straight body-design with soft grip
- \* Reversible
- \* Rear-exhaust, silenced
- \* ergonomic grip, lever start
- \* easily adjustable

### Related products



**HTB-0**  
Spring Balancer Hosereel

### Related accessories



**00-4507**  
Torque Adjust Key RRI screwdriver



### Specifications

| Brand                                     | RedRoosterIndustrial   |
|---|------------------------|
| Bolt capacity (mm)                        | 4                      |
| RPM                                       | 1100                   |
| Torque (Nm)                               | 1,5 - 4,0              |
| Airconsumption (l/s)                      | 10                     |
| Weight (kg)                               | 0,84                   |
| Hexagon                                   | 1/4"                   |
| Airconnection                             | PT 1/4"                |
| mm A                                      | 263                    |
| mm B                                      | 18                     |
| Hosediameter (mm)                         | 6,5                    |
| Execution                                 | Straight - lever start |
| Maximum Airpressure (Bar)                 | 6,3                    |
| Safety standard                           | EN ISO 11148-6         |
| Vibration standard                        | EN ISO 28927-2         |
| Vibration value (m/s <sup>2</sup> )       | 0,56                   |
| Vibration uncertainty (m/s <sup>2</sup> ) | 0,7                    |
| Sound standard                            | ISO 15744              |
| Sound pressure (dB(A))                    | 68,2                   |
| Sound uncertainty (dB(A))                 | 3                      |
| EAN                                       | 8717981279388          |