

AIR CHAIN HOIST 500KG 3MTR HOL TCS-500PE-3M


TCS-500 RED ROOSTER Air Chain Hoists are especially developed for the "Material Handling Industrie" for example: warehousing, packaging etc. These hoists have a very high lifting and lowering speed and are therefore also very well suitable for applications with long lifting hights.

Characteristics:

- Very high lifting and lowering speeds
- Maximum speed adjustable, lifting and lowering speed independent from each other
- Precise variable speed control
- Optimum control of the load, very precise positioning
- Compact and light weight.
- Exhaust hose easy to assemble
- Endstop system
- · Air motor is cooled by the exhaust air (internal)
- Pendant control
- Quiet, low noise level, silenced
- Aluminium housing

The price includes three meter of lift and two meter of control length, excluding the chain bucket.

Related accessories





Specifications

Number of chain falls 1 Lowering speed full load (m/min) 34 Lowering speed 0-load (m/min) 15,9 Lifting speed full load (m/min) 17 Lifting speed 0-load (m/min) 33 Chain weight (kg/m) 0,9 Chain (mm) 6,3 x 19,1 Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airconsumption fullload (l/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4" EAN 8717981391769	Brand	RedRooster
Lowering speed 0-load (m/min) Weight incl. 3m lift (kg) Lifting speed full load (m/min) Lifting speed 0-load (m/min) Chain weight (kg/m) Chain (mm) Chain (mm) Chainbag/Chainbucket Loadlimiter Airconnection Airpress max. (MPa) Airconsumption fullload (l/s) mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm J 22 mm J 22 mm Z Mm Z Hosediameter (mm) SMC Airtreatment unit Capacity (kg) Airconnection exhaust 3/4"	Number of chain falls	1
Weight incl. 3m lift (kg) Lifting speed full load (m/min) Lifting speed 0-load (m/min) Chain weight (kg/m) Chain (mm) Chainbag/Chainbucket Loadlimiter Airconnection Airpress max. (MPa) Airconsumption fullload (l/s) mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm J 22 mm Z Mm Z Hosediameter (mm) SMC Airtreatment unit Capacity (kg) Airconnection exhaust 3/4"	Lowering speed full load (m/min)	34
Lifting speed Gull load (m/min) 17 Lifting speed 0-load (m/min) 33 Chain weight (kg/m) 0,9 Chain (mm) 6,3 x 19,1 Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (l/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Lowering speed 0-load (m/min)	19
Lifting speed 0-load (m/min) 33 Chain weight (kg/m) 0,9 Chain (mm) 6,3 x 19,1 Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (l/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Weight incl. 3m lift (kg)	15,9
Chain weight (kg/m) 0,9 Chain (mm) 6,3 x 19,1 Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (l/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Lifting speed full load (m/min)	17
Chain (mm) 6,3 x 19,1 Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (I/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Lifting speed 0-load (m/min)	33
Chainbag/Chainbucket + Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (I/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Chain weight (kg/m)	0,9
Loadlimiter - Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (I/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Chain (mm)	6,3 x 19,1
Airconnection 1/2" BSPT Airpress max. (MPa) 0,63 Airconsumption fullload (I/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Chainbag/Chainbucket	+
Airpress max. (MPa) 0,63 Airconsumption fullload (I/s) 28,3 mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Loadlimiter	-
Airconsumption fullload (I/s) mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z Hosediameter (mm) SMC Airtreatment unit Capacity (kg) Airconnection exhaust 28,3 28,3 28,3 28,3 28,3 28,3 29,3 40 40 40 40 40 40 40 40 40 4	Airconnection	1/2" BSPT
mm A 415 mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Airpress max. (MPa)	0,63
mm B 255 mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	Airconsumption fullload (I/s)	28,3
mm C 132 mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm A	415
mm D 68 mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm B	255
mm E 205 mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm C	132
mm F 163 mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm D	68
mm G 15 mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm E	205
mm H 35 mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm F	163
mm I 22 mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm G	15
mm J 22 mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm H	35
mm X 40 mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm I	22
mm Z 210 Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm J	22
Hosediameter (mm) 13 SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm X	40
SMC Airtreatment unit AC40-F04DM-8-B Capacity (kg) 500 Airconnection exhaust 3/4"	mm Z	210
Capacity (kg) 500 Airconnection exhaust 3/4"	Hosediameter (mm)	13
Airconnection exhaust 3/4"	SMC Airtreatment unit	AC40-F04DM-8-B
7	Capacity (kg)	500
EAN 8717981391769	Airconnection exhaust	3/4"
	EAN	8717981391769

0 C