

AUTO-SHUT-OFF SCREWDRIVER 9,0~16NM ATEX RRI-SD50416-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIB T135°C.

Characteristics:

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, push-to-start
- easily adjustable

Related products



AC30A-F03E-B
Modular FRL Unit



HTB-1
Spring Balancer Hosereel

Related accessories



00-4507
Torque Adjust Key RRI screwdriver



ATLUB
Air Tool Oil, 1 litre



510R-027
Side Handle



Specifications

Brand	RedRoosterIndustrial
Bolt capacity (mm)	6
RPM	450
Torque (Nm)	9,0 - 16,0
Airconsumption (l/s)	11
Weight (kg)	1,29
Hexagon	1/4"
Sound level (dB(A))	74
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	309
mm B	45
mm C	16
mm D	15
Hosediameter (mm)	6,5
Execution	straight - push start
Vibration level (m/s ²)	< 2,5
Safety standard	EN ISO 11148-6
EAN	8717981460663

