

# AIR HAMMER VIBRATION REDUCED


















## RRH-4309K

The RED ROOSTER RRH-4309K is a strong and compact chipping hammer with high efficiency. The hammer is vibration reduced, has a quick change retainer and insulated handgrip to reduce user fatigue. The versatility of the hammer makes it suitable for professional use in various sectors.

#### Characteristics:

- Ergonomic design
- Quick change retainer
- Compact and lightweight
- Exhaust through handle
- For left and right handed use

#### Related products

-  **CB51193180**  
Slotting Tool W.Carbide Tip L=180
-  **RRH-4309KSET2**  
Air Hammer Kit Stone
-  **CB51112180**  
Flat Chisel
-  **CB51103185**  
45mm Wide Chisel,L=185mm
-  **CB51103250**  
Flat Chisel
-  **CB51109165**  
Flat Chisel
-  **CB51112250**  
Flat Chisel
-  **CB51116180**  
Tail Pipe Cutter
-  **CB51123180**  
Claw Ripper/PannelCutter
-  **CB51109180**  
Flat Chisel
-  **RRH-4309KSET1**  
Air Hammer Kit Metal
-  **CB51109250**  
Flat Chisel
-  **CB51102190**  
Scraper, bent
-  **CB51115250**  
Moil Point
-  **CB51109350**  
Flat Chisel L=350 W=20mm
-  **CB51115180**  
Moil point chisel
-  **CB51114180**  
Double Bladepanelcutter



#### Specifications

Brand	RedRooster
Airconsumption (l/s)	7,1
Weight (kg)	1,7
Shank size (mm)	H^11,0 x R^12,7 x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	223
mm B	173
Stroke (mm)	67
Strokes per minute	3200
Energy (J/Stroke)	9,0
Hosediameter (mm)	10
Piston (mm)	19
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	2,2
Vibration uncertainty (m/s <sup>2</sup> )	0,71
Sound standard	ISO 15744
Sound pressure (dB(A))	90,3
Sound power (dB(A))	101,3
Sound uncertainty (dB(A))	3
EAN	8717981362936

