

AIR HAMMER VIBRATION REDUCED RRH-4309K

The RED ROOSTER RRH-4309K is a strong and compact chipping hammer with high efficiency. The hammer is vibration reduced, has a quick change retainer and insulated handgrip to reduce user fatique. The versatility of the hammer makes it suitable for professional use in various sectors.

Characteristics:

- Ergonomic design
- Quick change retainer
- Compact and lightweight
- Exhaust through handle
- For left and right handed use

Related products

CB51193180

Slotting Tool W.Carbide Tip L=180

Air I

RRH-4309KSET2
Air Hammer Kit Stone

CB51112180 Flat Chisel

CB51103185

45mm Wide Chisel,L=185mm

CB51103250 Flat Chisel

CB51109165

Flat Chisel

CB51112250

Flat Chisel

CB51116180

Tail Pipe Cutter

CB51123180

Claw Ripper/PannelCutter

CB51109180 Flat Chisel

RRH-4309KSET1

Air Hammer Kit Metal

CB51109250

Flat Chisel

CB51102190

Scraper, bent

CB51115250

Moil Point

CB51109350

Flat Chisel L=350 W=20mm

CB51115180

Moil point chisel

CB51114180


Double Bladepanelcutter



Specifications

EAN

| Specifications | |
|------------------------------|----------------------|
| Brand | RedRooster |
| Airconsumption (I/s) | 7,1 |
| Weight (kg) | 1,7 |
| Shank size (mm) | H^11,0 x R^12,7 x 40 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 223 |
| mm B | 173 |
| Stroke (mm) | 67 |
| Strokes per minute | 3200 |
| Energy (J/Stroke) | 9,0 |
| Hosediameter (mm) | 10 |
| Piston (mm) | 19 |
| Safety standard | EN ISO 11148-4 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 2,2 |
| Vibration uncertainty (m/s²) | 0,71 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 90,3 |
| Sound power (dB(A)) | 101,3 |
| Sound uncertainty (dB(A)) | 3 |
| | |



8717981362936