

# SYSTEM WRENCH 3/8"

## TKA-70/L

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Product liability is essential to carmakers. All tightened joints have to be correct. For this reason all bolted joints must be counted, documented and, of course, tightened with the right clamping force. In order to do this, you need an impulse wrench (with a built-in transducer) connected to a controller. If the controller establishes that the tightened joints do not meet the specifications, it can give a line-stop signal and the joints have to be checked manually.

#### Characteristics:

- \* Very low weight / torque ratio
- \* High speed fastening
- \* No-lube airmotor
- \* No Kickback
- \* Green and Red LED signals on back-cover

#### Related products



**SKK**  
Tool Holder

#### Related accessories



0341-0018-00-00  
Hanger Ring Heavy Duty

0186-0029-00-00  
Rubber protection cover TKA60/70



#### Specifications

Brand	Yokota
Bolt capacity (mm)	6 - 8
RPM	7000
Torque (Nm)	20 - 35
Airconsumption (l/s)	5,3
Weight (kg)	1,3
Sound level (dB(A))	75
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	179
mm B	22
Hosediameter (mm)	6,5
Vibration level (m/s <sup>2</sup> )	2,1
Square Drive / Hexagon	3/8"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	6,9
EAN	8717981080427

