YOKOTA

CONTROLLED PRECISION IN TIGHTENING

IMPULSE WRENCH 3/8 SHUT-OFF 15-32NM YLTX70E

YOKOTA impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor and auto shut-off. No-lube airmotor.

Related accessories

0372-0029-00-00
Rubber protection cover YLT70



61022-TH002
Tool Holder, diameter 47mm



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	Yokota
Bolt capacity (mm)	6 - 8
RPM	6800
Torque (Nm)	15 - 32
Airconsumption (l/s)	6,0
Weight (kg)	1,01
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	177
mm B	23
Hosediameter (mm)	6,5
Square Drive / Hexagon	3/8"
Air consumption no load (l/s)	8,8
Vibration standard	EN ISO 28927-2
Vibration value (m/s^2)	< 2,5
Vibration uncertainty (m/s^2)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	74
Sound uncertainty (dB(A))	3
EAN	8717981356249

