

# IMPACT WRENCH 1-1/2 MI-5500ES

This industrial impact wrench by Toku has proven capabilities. The MI-5500ES is developed for tightening and untightening applications. The Dynapact hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact and strong
- \* Power adjustable, 4 positions

**Related products**



AC40A-F04-D  
Frl Unit

**Related accessories**



ATLUB  
Air Tool Oil, 1 litre



**Specifications**

Brand	Toku
Square Drive	1 1/2"
Version	H
Bolt capacity (mm)	52
Impact mechanism	Dynapact
RPM	2800
Torque (Nm)	5500
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	15,0
Weight (kg)	18,1
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	553
mm B	63
Hosediameter (mm)	13
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	9,7
Vibration uncertainty (m/s <sup>2</sup> )	0,71
Sound standard	ISO 15744
Sound pressure (dB(A))	100
Sound power (dB(A))	111
Sound uncertainty (dB(A))	3
EAN	8717981190966

