

# HIGH TORQUE GEAR WRENCH 4000 NM RRI-BEC400











RED ROOSTER Cordless high torque geared wrench. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility. Contactless trigger and forward / reverse switch for a long lifetime. This gear wrench has an extremely high speed.

#### Characteristics:

- Brushless motor
- 36 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque in 50 steps
- Display shows torque and setting
- automatic reaction arm release
- Tightening data retrievable via USB interface

Standard reaction arm is included. Delivered in plastic case with space available for two batteries and a charger. Batteries, charger and other accessories must be ordered separately.

#### Related accessories

-  SW40-283-0102  
Hanger
-  31084-360F  
36V Charger
-  DO6055S036  
High Torque Socket 1" x 36mm
-  33257-RRI-BEC400  
Reaction Bar
-  31022-GW025  
Reaction Welding ring for RRI-BEC400(S)
-  Koffer RRI-BEC400
-  Case RRI-BEC400
-  DO18715S  
Ret Ring
-  DO6055S065  
High Torque Socket 1"x 65mm
-  BB360F-350  
36V 5.0Ah Li-ion Battery



#### Specifications

Brand	RedRoosterIndustrial
Square Drive	1"
Bolt capacity (mm)	27 ~ 45
RPM	25 / 4,2
Torque (Nm)	800 ~ 4000
Weight w/o battery (kg)	8,2
mm A	177
mm B	87
mm C	380
mm D	228
mm E	260
mm F	Ø 90
mm L	90
Battery voltage (Volt)	36
Battery type Li-ion....(Ah)	5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	1
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	82
Sound uncertainty (dB(A))	3
EAN	8717981459063

