

CORDLESS SHUT-OFF ANGLE WRENCH

RRI-BA70S3

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

Characteristics:





- Brushless motor
- Lithium-Ion battery, choice for 2,5 Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Speed 160 RPM
- Compact and light weight

Battery and charger to be ordered separately. The reaction bar 31022-WR00 is included in the delivery.

Related products

- | | |
|---|--|
|  | BB200D-325
18V 2.5Ah Battery, Li-ion |
|  | B74SC180B
Programmer |
|  | BB200D-350
18V 5.0Ah Battery, Li-ion |
|  | B84192B
18-20V Charger |
|  | E86B-VD
Power Cord (EU) |

Related accessories

- | | |
|---|---|
|  | 33116-B200D-01
Protection Cover |
|  | 61022-TH005
Tool Holder |
|  | 33116-B200D-02
Protection Cover |
| | 31022-WR00
Reaction Bar for RRI-BA70/90 |
|  | 00-4507
Torque Adjust Key RRI screwdriver |
| | C16WRB70
Protection Cover RRI-BA70 |



Specifications

Brand	RedRoosterIndustrial
Square Drive	3/8"
Bolt capacity (mm)	8 - 12
RPM	160
Torque (Nm)	30 - 70
Weight w/o battery (kg)	2,5
mm A	535
mm B	50
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,5 - 5,0
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	18
Vibration uncertainty (m/s ²)	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	69,2
Sound uncertainty (dB(A))	3
EAN	8717981337514

