

IMPACT WRENCH 3/8 MI-16M3/8

This TOKU Impact Wrench has an excellent weigth/power ratio. The MI-16 is developed for assembly- and disassembly purposes. The Twin Hammer impactmechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer

Related products



D0605121301

Impact Socket Set 3/8" deep 13-parts



D0611101301

Impact Socket Set 3/8" 13-parts

Related accessories



ATLUB

Air Tool Oil, 1 litre



Specifications

RPM

Brand	Toku
Square Drive	3/8"
Version	R
Bolt capacity (mm)	12

Impact mechanism Twin-Hammer

6200

Torque (Nm) 270
Force adjustment R/L 4 Standen
Airconsumption (I/s) 9.3

 Airconsumption (I/s)
 9,3

 Weight (kg)
 1,5

 Airconnection
 PT 1/4"

 Airpress max. (MPa)
 0,63

 mm A
 170

 mm B
 27

 Hosediameter (mm)
 6,5

Safety standard EN ISO 11148-6 Vibration standard EN ISO 28927-2

Vibration value (m/s²) 6,9

Vibration uncertainty (m/s²) 1,18

Sound standard ISO 15744

Sound pressure (dB(A)) 89

Sound power (dB(A)) 100

Sound uncertainty (dB(A)) 3

EAN 8717981324590

