

# IMPACT WRENCH 1" MI-3800ELR

This industrial impact wrench by Toku has proven capabilities. The MI-3800ELR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* Power adjustable, 4 positions
- \* Long anvil

**Related products**



**D00100-1-007**  
Impact Socket Set Long 1" 7-parts

**Related accessories**



**ATLUB**  
Air Tool Oil, 1 litre



**DOESR-3**  
Ret Ring



**Specifications**

<b>Brand</b>	Toku
<b>Square Drive</b>	1"
<b>Version</b>	R+H
<b>Bolt capacity (mm)</b>	36
<b>Impact mechanism</b>	Gesloten Hamer
<b>RPM</b>	4500
<b>Torque (Nm)</b>	2000
<b>Force adjustment</b>	R/L 4 Standen
<b>Airconsumption (l/s)</b>	15
<b>Weight (kg)</b>	9,9
<b>Airconnection</b>	PT 1/2"
<b>Airpress max. (MPa)</b>	0,63
<b>mm B</b>	55
<b>Hosediameter (mm)</b>	13
<b>mm A*</b>	504
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	10,4
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,52
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	96
<b>Sound power (dB(A))</b>	107
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981000197

