

IMPACT WRENCH 1" MI-3800ELR

This industrial impact wrench by Toku has proven capabilities. The MI-3800ELR is developed for tightening and untightening apllications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for use in the industry. Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable, 4 positions
- * Long anvil

Related products



D00100-1-007 Impact Socket Set Long 1" 7-parts



AC40A-F04-D Frl Unit

Related accessories



AILUB

Air Tool Oil, 1 litre



DOESR-3 Ret Ring



Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	36

Impact mechanism Gesloten Hamer

RPM 4500 Torque (Nm) 2000

Force adjustment R/L 4 Standen

 Airconsumption (I/s)
 15

 Weight (kg)
 9,9

 Airconnection
 PT 1/2"

 Airpress max. (MPa)
 0,63

 mm B
 55

 Hosediameter (mm)
 13

 mm A*
 504

Safety standard EN ISO 11148-6 Vibration standard EN ISO 28927-2

Vibration value (m/s²) 10,4

Vibration uncertainty (m/s²) 1,52

Sound standard ISO 15744

Sound pressure (dB(A)) 96

Sound power (dB(A)) 107

Sound uncertainty (dB(A)) 3

EAN 8717981000197

