

IMPULSE WRENCH 3/8 SHUT-OFF YLTX80E

YOKOTA impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor and auto shut-off. No-lube airmotor.

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories

0373-0029-00-00

Rubber protection cover YLT-80



61022-TH003
Tool Holder, diameter 58mm



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	Yokota
Bolt capacity (mm)	8
RPM	6800
Torque (Nm)	30 - 55
Airconsumption (l/s)	7,3
Weight (kg)	1,12
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	187
mm B	24,5
Hosediameter (mm)	9,5
Square Drive / Hexagon	3/8"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	9,2
Formal Capacity	30 - 55
Formal Serie From	0P0001
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	< 2,5
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	78
Sound uncertainty (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	002
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981356256

