












# HAMMER Ø25X75/SCREW CAP HOLDER RRI-4596R

This RED ROOSTER picking hammer has a screw cap holder for the chisels. Suitable for endured usage. High energy level each blow. For applications in construction and renovations.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact quality tool
- \* Suits lefthanders and righthanders

**Related products**

-  **B600MP**  
Moil Point TL=675
-  **B1000NC**  
Flat Chisel TL=1100 W=24
-  **B1000MP**  
Moil Point TL=1000
-  **B1500MP**  
Moil Point TL=1500
-  **B2000MP**  
Moil Point TL=2000
-  **B350NC**  
Flat Chisel TL=425 W=24
-  **B350MP**  
Moil Point TL= 425
-  **B800MP**  
Moil Point TL=875
-  **B450NC**  
Flat Chisel TL=535 W=24
-  **B450MP**  
Moil Point TL= 535
-  **B600NC**  
Flat Chisel TL=675 W=24

**Related accessories**

-  **4596-022-01**  
Cylinder Cover (open)
-  **4596-022-02**  
Cylinder Cover (closed)



**Specifications**

<b>Brand</b>	RedRoosterIndustrial
<b>Airconsumption (l/s)</b>	15,0
<b>Weight (kg)</b>	9,7
<b>Shank size (mm)</b>	R^25 x 75
<b>Airconnection</b>	PT 3/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	480
<b>mm B</b>	118
<b>Stroke (mm)</b>	114
<b>Strokes per minute</b>	1590
<b>Energy (J/Stroke)</b>	51,6
<b>Hosediameter (mm)</b>	13
<b>Piston (mm)</b>	34
<b>Vibration standard</b>	EN ISO 28927-10
<b>Vibration value (m/s<sup>2</sup>)</b>	14,5
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,2
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	84
<b>Sound power (dB(A))</b>	105
<b>Sound uncertainty (dB(A))</b>	1,2
<b>EAN</b>	8717981104574

