

# 18V-3/8" SQ, TRANSDUCER NUTRUNNER

## RRI-BCA10S3

RED ROOSTER Cordless transducerized angle wrench. Very well suited for assembly applications where good torque accuracy is required. 8 programs can be set for both torque and angular displacement. The programs can be easily selected or programmed in a fixed sequence. Contactless trigger and forward / reverse switch for a long lifetime. Repeatability Cm/Cmk > 2 at +/- 7%.

#### Characteristics:

- Brushless motor
- 18 Volt Lithium-Ion battery
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Tightening mode setting – Torque or Angle
- Programmable torque
- Programmable angle limits
- Programmable speed
- Group check / counting
- 8 programs including sequence
- Compact and light weight
- The flat battery pack offers stability
- Battery (2,5 Ah: BB200D-325; 5,0 Ah: BB200D-350) and charger (B84192B) to be ordered separately

#### Related products

	<b>BB200D-325</b>
	18V 2.5Ah Battery, Li-ion
	<b>BB200D-350</b>
	18V 5.0Ah Battery, Li-ion
	<b>B84192B</b>
	18-20V Charger

#### Related accessories

	<b>33116-B200D-01</b>
	Protection Cover
	<b>61022-TH005</b>
	Tool Holder
	<b>32088-NPA-01</b>
	Cable
	<b>33116-B200D-02</b>
	Protection Cover
	<b>33116-NRA-01</b>
	Protection Cover RRI-BCA16&30



#### Specifications

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>Square Drive</b>	<b>3/8"</b>
<b>Bolt capacity (mm)</b>	<b>6</b>
<b>RPM</b>	<b>150 - 750</b>
<b>Torque (Nm)</b>	<b>4 - 10</b>
<b>Weight w/o battery (kg)</b>	<b>1,68</b>
<b>mm A</b>	<b>438,9</b>
<b>mm B</b>	<b>38</b>
<b>Battery voltage (Volt)</b>	<b>18</b>
<b>Battery type Li-ion....(Ah)</b>	<b>2,5 / 5,0</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>&lt; 75</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981422678</b>

