

REFRIGERATED AIR DRYER IDFA15E1-23-K

The SMC IDFA Series of refrigerated air dryers are the result of over 40 years of experience combined with the latest compressed air and refrigeration technology. Built according to international standards and recognized by SMC's BS EN ISO 9001 quality certification. The IDFA Series has thirteen standard models with nominal capacities ranging from 12 - 1.340 m3/h.

- Innovative design ensures a constant +3 degrees °C pressure dew point
- · High efficiency heat exchanger
- Environmentally ozone friendly refrigerants
- Conforms to stringent ISO8573-1 standard
- Simple control system with easy to read evaporator gauge
- Compact design for easy installation
- High performance, reliable and trouble-free



Specifications

Brand	SMC
Weight (kg)	46
Refrigerant	R134a
Airconnection	Rc 1
Airpress max. (MPa)	0,15 - 1,6
mm A	300
mm B	603
mm C	578
Ambient temp.	2 - 40
Power cons. (W)	470
Inlet air temperature	5 - 50

Power Supply (V) 1 Phase 230 V AC 50/60 Hz

Flowrate at 3°C Pressure dew point 120 Flowrate at 7°C Pressure dew point 152 Flowrate at 10°C Pressure dew point 168

EAN 8717981365111