

AUTO-SHUT-OFF SCREWDRIVER RRI-SA10902

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- * New angled body-design with soft grip
- * Reversible
- * Rear-exhaust, silenced
- * ergonomic grip, lever start
- * easily adjustable

Related products



AC30A-F03E-B Modular FRL Unit

Related accessories

\$ 00-4507

Torque Adjust Key RRI screwdriver ATLUB Air Tool Oil, 1 litre



Specifications

| Brand | RedRoosterIndustrial |
|------------------------------|----------------------|
| Bolt capacity (mm) | 4 |
| RPM | 900 |
| Torque (Nm) | 0,4 - 1,8 |
| Airconsumption (I/s) | 8 |
| Weight (kg) | 0,82 |
| Hexagon | 1/4" |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 294 |
| mm B | 29 |
| mm C | 16,1 |
| mm D | |
| mm E | 12 |
| Hosediameter (mm) | 6,5 |
| Execution | Angle |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s²) | 0,3 |
| Vibration uncertainty (m/s²) | 0,53 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 68,1 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981279104 |
| | |

