

AUTO-SHUT-OFF SCREWDRIVER 24~45NM ATEX RRI-SA60945W-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIB T135°C.

Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

Related products



TW-3C

Spring balancer 1,0-3,0 kg



AC30A-F03E-B

Modular FRL Unit

Related accessories



00-4507

Torque Adjust Key RRI screwdriver



ATLUB

Air Tool Oil, 1 litre



Specifications

| | |
|-------------------------------------|----------------------|
| Brand | RedRoosterIndustrial |
| Square Drive | 1/2" |
| Bolt capacity (mm) | 8 |
| RPM | 90 |
| Torque (Nm) | 24 ~ 45 |
| Airconsumption (l/s) | 11 |
| Weight (kg) | 2,09 |
| Sound level (dB(A)) | 74 |
| Airconnection | PT 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 411 |
| mm B | 34 |
| mm C | 19 |
| mm D | 18,5 |
| mm E | 1/2" |
| Hosediameter (mm) | 6,5 |
| Execution | Angle |
| Vibration level (m/s ²) | < 2,5 |
| Safety standard | EN ISO 11148-6 |
| EAN | 8717981461066 |

