

# AIR CHAIN HOIST 6000 KG TMH-6000LFC2

The new RED ROOSTER LF series of lubrication free hoists is the latest addition in a line of new models within the Red Rooster air hoist range. The oil free operation allows the hoist to run whilst preventing any oil being exhausted into the atmosphere, making the units ideal for use where a clean environment is a requirement. These new air hoists are suitable for food, chemical, pharmaceutical and painting industries.


#### CHARACTERISTICS:

- Precise variable speed control
- Optimum control of the load
- Robust and reliable
- Mechanical end stop
- High quality RUD hoist chain
- Full load supporting eye for safe installation
- Standard delivered including ATEX zone 2 certificate

#### OPTIONS:

- Paint systems for C5 Marine
- Zone 1 ATEX certification
- Chain collectors
- Hook or clevis options
- Air supply systems and valves

#### Related products



#### Specifications

Brand	RedRooster
Number of chain falls	2
Lowering speed full load (m/min)	2,8
Lowering speed 0-load (m/min)	1,6
Weight incl. 3m lift (kg)	124
Lifting speed full load (m/min)	1,6
Lifting speed 0-load (m/min)	3,2
Chain weight (kg/m)	3,8
Chain (mm)	13 x 36
Airconnection	1" BSPT
Airconsumption fullload (l/s)	51
mm A	742
mm B	371
mm C	245
mm D	126
mm E	265
mm F	311
mm H	65
mm I	42
Hosediameter (mm)	19
SMC Airtreatment unit	AW60-F10DE-B
Workingpressure (MPa)	0,4 - 0,63
Capacity (kg)	6000
Formal Capacity	6000
Airconnection exhaust	1"
Sales Group	015
UNSPSC number	24101602
Eclass number	36120206
EAN	8717981389315