

# MANIPULATOR 125 KG TCR-125ME

The RED ROOSTER Compact Hoist are suitable for "Material-Handling".  
The pendant control is direct on the lower hook so the operator can control and position the load easy and direct.  
Lifting height 3 meters. The perfect solution for horizontal movements is the combination with a push trolley.

**Characteristics:**

- Pendant control direct on the lower hook
- Optimum load control, very precise positioning
- One-hand control
- Variable speed control
- Soft start and stop, no shock movements
- Handle can be positioned for left-hand or right-hand operation
- Endstop system

**Related products**



**4X12RTS**

Chain RTS EN 818-7



**4X12RS60**

Chain RS60 Stainless Steel EN818-7



**Specifications**

<b>Brand</b>	RedRooster
<b>Number of chain falls</b>	1
<b>Lowering speed full load (m/min)</b>	14
<b>Lowering speed 0-load (m/min)</b>	12,4
<b>Weight incl. 3m lift (kg)</b>	11
<b>Lifting speed full load (m/min)</b>	10
<b>Lifting speed 0-load (m/min)</b>	16
<b>Chain weight (kg/m)</b>	0,35
<b>Chain (mm)</b>	4,0 x 12,0 (HD)
<b>Chainbag/Chainbucket</b>	+
<b>Loadlimiter</b>	-
<b>Trolley</b>	+
<b>Airconnection</b>	3/8" BSPT
<b>Airpress max. (MPa)</b>	0,63
<b>Airconsumption fullload (l/s)</b>	11,7
<b>mm A</b>	286
<b>mm B</b>	174
<b>mm C</b>	112
<b>mm D</b>	837
<b>mm E</b>	15
<b>mm F</b>	194
<b>mm G</b>	102
<b>mm H</b>	92
<b>mm I</b>	184
<b>mm J</b>	123
<b>mm K</b>	61
<b>mm L</b>	152
<b>mm M</b>	74
<b>mm N</b>	78
<b>mm O</b>	36
<b>Hosediameter (mm)</b>	13
<b>SMC Airtreatment unit</b>	AC30-F03DM-8-B
<b>Capacity (kg)</b>	125