

# COMPOSITE IMPACT WRENCH 1/2 ATEX

## RRI-1400M-EX

This stubby composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-1400M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use.

Breakloose torque: 1.200 Nm.

ATEX classification Ex II 3G IIB T4 – Ex II 3D IIIB 135°C

#### Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- Power adjustable, 2 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown

#### Related products

DO2012-0-013-EX

Socket 1/2" x 13 ATEX



AC30A-F03E-B

Modular FRL Unit



DO2012-0-019-EX

Socket 1/2" x 19 ATEX

DO2012-0-032-EX

Socket 1/2" x 32 ATEX

#### Related accessories



ATLUB

Air Tool Oil, 1 litre



#### Specifications

Brand	RedRoosterIndustrial
Square Drive	1/2"
Version	R
Bolt capacity (mm)	14
Impact mechanism	Mechoneer
RPM	9000
Torque (Nm)	470
Force adjustment	R 2 Pos
Airconsumption (l/s)	8,5
Weight (kg)	1,3
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	120
mm B	35
Hosediameter (mm)	6,5
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	1200
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	4,5
Vibration uncertainty (m/s <sup>2</sup> )	0,94
Sound standard	ISO 15744
Sound pressure (dB(A))	87
Sound power (dB(A))	98
Sound uncertainty (dB(A))	3
EAN	8717981459773

