RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

COMPOSITE IMPACT WRENCH ½ ATEX RRI-1400M-EX

This stubby composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-1400M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use.
Breakloose torque: 1.200 Nm.
ATEX classification Ex II 3G IIB T4 – Ex II 3D IIIB 135°C

Characteristics:
- **Ergonomic design, well balanced**
- **Compact and lightweight**
- **Mechoneer Impact mechanism**
- **Power adjustable, 2 positions forward**
- **Exhaust silenced, through grip**
- **Forward/Reverse lever on trigger, for one-hand operation**
- **2-Step trigger for controlled rundown**

Related products



DO2012-0-013-EX
Socket 1/2" x 13 ATEX



DO2012-0-019-EX
Socket 1/2" x 19 ATEX



DO2012-0-032-EX
Socket 1/2" x 32 ATEX

Related accessories



EH-43-4033SUB
Exhaust Hose Assembly 1/4"



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	**RedRoosterIndustrial**
Square Drive	**1/2"**
Version	**R**
Bolt capacity (mm)	**14**
Impact mechanism	**Mechoneer**
RPM	**9000**
Torque (Nm)	**470**
Force adjustment	**R 2 Pos**
Airconsumption (l/s)	**8,5**
Weight (kg)	**1,3**
Airconnection	**PT 1/4"**
Airpress max. (MPa)	**0,63**
mm A	**120**
mm B	**35**
Hosediameter (mm)	**6,5**
Max. breakaway torque (Nm)	**1200**
Vibration standard	**EN ISO 28927-2**
Vibration value (m/s²)	**4,5**
Vibration uncertainty (m/s²)	**0,94**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**87**
Sound power (dB(A))	**98**
Sound uncertainty (dB(A))	**3**
EAN	**8717981459773**

