

# IMPACT WRENCH 3/8"

## MI-12

This TOKU Impact Wrench has an excellent weight/power ratio. The MI-12 is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

### Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer



### Related products

	<b>D0605121301</b>
	Impact Socket Set 3/8" deep 13-parts
	<b>AC30A-F03E-D</b>
	Frl Unit
	<b>D0611101301</b>
	Impact Socket Set 3/8" 13-parts

### Related accessories

	<b>ATLUB</b>
	Air Tool Oil, 1 litre

### Specifications

<b>Brand</b>	<b>Toku</b>
<b>Square Drive</b>	<b>3/8"</b>
<b>Version</b>	<b>R</b>
<b>Bolt capacity (mm)</b>	<b>12</b>
<b>Impact mechanism</b>	<b>Twin-Hammer</b>
<b>RPM</b>	<b>9500</b>
<b>Torque (Nm)</b>	<b>160</b>
<b>Force adjustment</b>	<b>R/L 4 Stufen</b>
<b>Airconsumption (l/s)</b>	<b>5,3</b>
<b>Weight (kg)</b>	<b>1,2</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>150</b>
<b>mm B</b>	<b>24</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Safety standard</b>	<b>EN ISO 11148-6</b>
<b>Vibration standard</b>	<b>EN ISO 28927-2</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>5,9</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>1,08</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>87</b>
<b>Sound power (dB(A))</b>	<b>98</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981000142</b>

