

# ANGLE GRINDER 180MMX22MM G-70EF

This angled grinder by Yokota is used for grinding and cutting. Very high quality level. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal.

#### Characteristics:

- \* Ergonomic design, well balanced
- \* Compact and lightweight
- \* For cutting and grinding purposes
- \* Exhaust silenced
- \* Vibrationreduced deadhandle

#### Related accessories

-  1508-0655-00-00  
Outer Wheel Screw
-  9310-3006-00-99  
Rubber Pad (178) With Flange
-  1508-0653-00-03  
Inner Flange
-  1407-0013-00-11  
Dead Handle Vibration Red.
-  8100-4003-00-01  
Hook Wrench
-  9310-3006-00-00  
Rubber pad G-70/7VC-6500/7VC-8500
-  1508-0654-05-05  
Pad Flange
-  1508-0654-00-01  
Outer Flange
-  1508-0653-01-02  
Inner Flange
-  1422-0653-00-99  
Inner Flange
-  ATLUB  
Air Tool Oil, 1 litre
-  8100-5002-00-00  
Twin Wrench G70EF/7VC-6500/7VC-8500
-  1508-0654-00-02  
Outer Flange



#### Specifications

Brand	Yokota
RPM	8500
Airconsumption (l/s)	16,7
Weight (kg)	2,9
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	341
mm B	107
mm C	37
mm D	60
Hosediameter (mm)	13
Spindle	5/8"
Power (kW)	1,12
Wheel size (mm)	180 x (1,6 - 8) x 22,2
Vibration standard	EN ISO 28927-1
Vibration value (m/s <sup>2</sup> )	2,7
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	85
Sound power (dB(A))	96
Sound uncertainty (dB(A))	3
EAN	8717981000098

