

# POWER CUTTER

## RRI-8004

Power cutters have simplified cutting and pressing in mass production. Versatile applications of the power cutter by selection of suitable blades, make it possible to increase production.

The working pressure is 4 - 5 bar.

Blades for power cutters are delivered separately.

### Related products



**FD-5**

**Blade for Power Cutter RRI-8004**



**CR-6**

**Blade for Power Cutter RRI-8004**



**EP-6**

**Blade for Power Cutter RRI-8004**



**S-5**

**Blade for Power Cutter RRI-8004**



**F-5**

**Blade for Power Cutter RRI-8004**



**Z-6**

**Blade for Power Cutter RRI-8004**



**P-6**

**Blade for Power Cutter RRI-8004**



### Specifications

|                                       |                             |
|---------------------------------------|-----------------------------|
| <b>Brand</b>                          | <b>RedRoosterIndustrial</b> |
| <b>Weight (kg)</b>                    | <b>0,34</b>                 |
| <b>Capacity copper (mm)</b>           | <b>2,6</b>                  |
| <b>Capacity crimping (mm)</b>         | <b>-</b>                    |
| <b>Capacity plastics (mm)</b>         | <b>7,0</b>                  |
| <b>Capacity steel (mm)</b>            | <b>2,0</b>                  |
| <b>Sound level (dB(A))</b>            | <b>73</b>                   |
| <b>Airconnection</b>                  | <b>PT 1/4"</b>              |
| <b>Airpress max. (MPa)</b>            | <b>0,5</b>                  |
| <b>Airconsumption (liter per cut)</b> | <b>0,230</b>                |
| <b>mm A</b>                           | <b>156</b>                  |
| <b>mm B</b>                           | <b>45</b>                   |
| <b>Power midway on blade (kg)</b>     | <b>140</b>                  |
| <b>Hosediameter (mm)</b>              | <b>6,5</b>                  |
| <b>Vibration level (m/s²)</b>         | <b>0,3</b>                  |
| <b>Safety standard</b>                | <b>EN ISO 11148-2</b>       |
| <b>EAN</b>                            | <b>8717981031405</b>        |

