

# CHIPPING HAMMER H19X50 THA-3BRH19X50

Toku hammers have been used for many years in various industries, e.g Demolition, Foundries, Construction etc.

**Characteristics:**

- \* Toku only use the very best materials in the manufacture of their products giving the tools superior life.
- \* Due to popular demand we have included a version of this tool to our range with a solid retainer.
- \* The design of the solid retainer enables the use of pointed chisels as well as standard and wide.

**Related products**

- CB5-G  
Wide Chisel bend TL=250 W=60
- CB5  
Wide Chisel TL=300 B=60
- MP5-350  
Moil Point TL= 400mm
- MP5  
Moil Point TL= 325mm
- NC5-450  
Flat Chisel TL=500 W=22
- MP5-450  
Moil Point TL= 500mm
- NC5-350  
Flat Chisel TL=400 W=22
- NC5  
Flat Chisel TL=325 W=22



**Specifications**

Brand	Toku
Airconsumption (l/s)	15
Weight (kg)	7,2
Shank size (mm)	H <sup>19</sup> x 50
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	422
mm B	87
Stroke (mm)	64
Strokes per minute	2300
Energy (J/Stroke)	19,9
Hosediameter (mm)	13
Piston (mm)	28,5
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-10
Vibration value (m/s <sup>2</sup> )	30,1
Vibration uncertainty (m/s <sup>2</sup> )	3,30
Sound standard	ISO 15744
Sound pressure (dB(A))	110
Sound power (dB(A))	121
Sound uncertainty (dB(A))	3
EAN	8717981214198

