

# NEEDLE SCALER TFC-N200

This Toku needle-scaler is developed for operations of longer use, has an extremely high frequency and is meant for industrial use.

**Characteristics:**

- \* Good ergonomics, well balanced
- \* For lefthanded as well as righthanded use
- \* Easy exchange of needles

**Related accessories**

Y3-06-12-210

Needle 3Mmx125L



**Specifications**

<b>Brand</b>	<b>Toku</b>
<b>Airconsumption (l/s)</b>	<b>4,1</b>
<b>Weight (kg)</b>	<b>1,12</b>
<b>Number 2 mm</b>	<b>21</b>
<b>Number 3 mm</b>	<b>12</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>273</b>
<b>mm B</b>	<b>36</b>
<b>Stroke (mm)</b>	<b>10,0</b>
<b>Strokes per minute</b>	<b>12000</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Piston (mm)</b>	<b>20,0</b>
<b>Safety standard</b>	<b>EN ISO 11148-4</b>
<b>Vibration standard</b>	<b>EN ISO 28927-9</b>
<b>Vibration value (m/s<sup>2</sup>)</b>	<b>13,3</b>
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	<b>0,69</b>
<b>Sound standard</b>	<b>ISO 15744</b>
<b>Sound pressure (dB(A))</b>	<b>92</b>
<b>Sound power (dB(A))</b>	<b>103</b>
<b>Sound uncertainty (dB(A))</b>	<b>3</b>
<b>EAN</b>	<b>8717981062553</b>

