

# AIR HAMMER KIT METAL RRH-4312KSET1

The RED ROOSTER RRH-4312K is a strong and compact chipping hammer with high efficiency. The hammer is vibration reduced, has a quick change retainer and insulated handgrip to reduce user fatigue. The versatility of the hammer makes it suitable for professional use in various sectors.












#### Characteristics:

- Ergonomic design
- Quick change retainer
- Compact and lightweight
- Exhaust through handle
- For left and right handed use



#### Set includes 5 chisels:

Flat chisel - CB51109180  
Spotweld Breaker - CB51117180  
Double Bladepanelcutter - CB51114180  
Claw Ripper/PannelCutter - CB51123180  
Tail Pipe Cutter - CB51116180

#### Related products

-  CB51193180  
Slotting Tool W.Carbide Tip L=180
-  CB51112180  
Flat Chisel
-  CB51103185  
45mm Wide Chisel,L=185mm
-  CB51103250  
Flat Chisel
-  CB51109165  
Flat Chisel
-  CB51112250  
Flat Chisel
-  CB51109250  
Flat Chisel
-  CB51102190  
Scraper, bent
-  CB51109350  
Flat Chisel L=350 W=20mm
-  CB51115180  
Moil point chisel
-  CB51104190  
Wide Cuttingchisbent

#### Related accessories

-  TJI-207  
Retainer Spring RRH-4309,RRH-4312
-  TJI-202A  
Quick Change Retainer



#### Specifications

Brand	RedRooster
Airconsumption (l/s)	7,1
Weight (kg)	1,8
Shank size (mm)	H^11,0 x R^12,7 x 40
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	267
mm B	173
Stroke (mm)	89
Strokes per minute	2100
Energy (J/Stroke)	12,0
Hosediameter (mm)	10
Piston (mm)	19
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-9
Vibration value (m/s <sup>2</sup> )	2,6
Vibration uncertainty (m/s <sup>2</sup> )	0,75
Sound standard	ISO 15744
Sound pressure (dB(A))	90,9
Sound power (dB(A))	101,9
Sound uncertainty (dB(A))	3
EAN	8717981362974

