

ANGLE GRINDER, 125 X 22MM RRI-G50HP25

This angled grinder by RED ROOSTER is used for grinding and cutting. Very high quality level. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal. The air motor has a very high power of 1,87 kW, enabling more material removal. The M14 spindle can be held by push button for easy exchange of accessories like grinding discs. The guard cover can be adjusted easily, without a need for tools.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- For cutting and grinding purposes
- The M14 spindle allows use of standardized wire brushes and 3M Cubitron support pad
- Rear exhaust silenced
- Vibration reducing side handle
- Included exhaust hose for noise reduction

Related products



AC40A-F04-D Modular FRL unit

Related accessories



2400-046-11

Dead Handle Vibration Red.



QN-M14

Quick Nut M14X2.0P



ATLUB

Air Tool Oil, 1 litre



Specifications

Brand	RedRoosterIndustrial
RPM	12000
Airconsumption (I/s)	26
Weight (kg)	1,83
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	227,3
mm B	143,1
mm C	49,9
mm D	31,6
Hosediameter (mm)	13
Spindle	M14 x 2
Power (kW)	1,87
Wheel size (mm)	125 x (0,8-7) x 22,2
Safety standard	EN ISO 11148-7
Vibration standard	EN ISO 28927-1
Vibration value (m/a2)	0.50

Vibration value (m/s²) 9,59

Vibration uncertainty (m/s²) 1,44

Sound standard ISO 15744

Sound pressure (dB(A)) 91

Sound power (dB(A)) 102

Sound uncertainty (dB(A)) 3

EAN 8717981439225

