

# CORDLESS SHUT-OFF ANGLE WRENCH 90 NM RRI-BAW90S4

RED ROOSTER cordless angle wrench with automatic shut-off. Very well suited for assembly applications with a need of good torque accuracy. Especially in areas where cables and hoses impede handling flexibility, such as interiors of cars, coaches and trains.

#### Characteristics:





- Brushless motor
- Lithium-Ion battery, choice for 2,5 Ah or 5,0 Ah capacity
- LED status indicates OK - NOK - REVERSE - BATTERY LOW
- Adjustable torque
- Compact and light weight

Battery and charger to be ordered separately. The reaction bar 31022-WR00 is included in the delivery.

#### Related products

	<b>DWL-B</b> 2.4G/5.8G WLAN receiver
	<b>BB200D-325</b> 18V 2.5Ah Battery, Li-ion
	<b>B74SC180B</b> Programmer
	<b>BB200D-350</b> 18V 5.0Ah Battery, Li-ion
	<b>B84192B</b> 18-20V Charger

#### Related accessories

	<b>33116-B200D-01</b> Protection Cover
	<b>61022-TH005</b> Tool Holder
	<b>33116-B200D-02</b> Protection Cover
	<b>31022-WR00</b> Reaction Bar for RRI-BA70/90
	<b>00-4507</b> Torque Adjust Key RRI screwdriver
	<b>C16WRB70</b> Protection Cover RRI-BA70



#### Specifications

<b>Brand</b>	RedRoosterIndustrial
<b>Square Drive</b>	1/2"
<b>Bolt capacity (mm)</b>	8 - 12
<b>RPM</b>	90
<b>Torque (Nm)</b>	30 - 90
<b>Weight w/o battery (kg)</b>	2,5
<b>mm A</b>	535
<b>mm B</b>	50
<b>Battery voltage (Volt)</b>	18
<b>Battery type Li-ion....(Ah)</b>	2,5 - 5,0
<b>Safety standard</b>	EN ISO 11148-6
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	25,3
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,5
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	67,4
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981452859

