

# DOWEL PIN PULLER

## YDP-20

The Yokota dowel pin puller is used in matrix, casting and press-moulding industries, for setting and removing dowel pins in moulds or presses. The dowel pin puller is an easily operated air tool and can simplify the pulling or hammering operation

of the threaded dowel pins, saving time and improving working efficiency.

Delivered including:

M8 x 50L: 6503-0022-00-13,

M10 x 50L: 6503-0022-00-14 and

M12 x 50L: 6503-0022-00-15.

### Related accessories

- 6503-0022-00-13  
Hanger Bolt M8 X 50L
- 6503-0022-00-11  
Hanger Bolt M12X150L
- 6503-0022-00-10  
Hanger Bolt M12X100L
- 6503-0022-00-05  
Hanger Bolt M8 X150L
- 6503-0022-00-09  
Hanger Bolt M10X200L
- 6503-0022-00-06  
Hanger Bolt M8 X200L
- 6503-0022-00-12  
Hanger Bolt M12X200L
- 6503-0022-00-14  
Hanger Bolt M10X 50L
- 6503-0022-00-08  
Hanger Bolt M10X150L
- 6503-0022-00-07  
Hanger Bolt M10X100L
- 6503-0022-00-15  
Hanger Bolt M12X 50L
- 6503-0022-00-04  
Hanger Bolt M8 X100L



### Specifications

Brand	Yokota
Airconsumption (l/s)	4,3
Weight (kg)	2,10
Capacity pin (mm)	20
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	195
mm B	82
Stroke (mm)	36 x 33
Strokes per minute	2700
Hosediameter (mm)	6,5
Vibration standard	EN ISO 28927-9
Vibration value (m/s <sup>2</sup> )	8
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	95
Sound power (dB(A))	106
Sound uncertainty (dB(A))	3
EAN	8717981147908

