

# DOWEL PIN PULLER

## YDP-20

The Yokota dowel pin puller is used in matrix, casting and press-moulding industries, for setting and removing dowel pins in moulds or presses. The dowel pin puller is an easily operated air tool and can simplify the pulling or hammering operation of the threaded dowel pins, saving time and improving working efficiency.

### Related accessories

- 6503-0022-00-13  
Hanger Bolt M8 X 50L
- 6503-0022-00-11  
Hanger Bolt M12X150L
- 6503-0022-00-10  
Hanger Bolt M12X100L
- 6503-0022-00-05  
Hanger Bolt M8 X150L
- 6503-0022-00-09  
Hanger Bolt M10X200L
- 6503-0022-00-06  
Hanger Bolt M8 X200L
- 6503-0022-00-12  
Hanger Bolt M12X200L
- 6503-0022-00-14  
Hanger Bolt M10X 50L
- 6503-0022-00-08  
Hanger Bolt M10X150L
- 6503-0022-00-07  
Hanger Bolt M10X100L
- 6503-0022-00-15  
Hanger Bolt M12X 50L
- 6503-0022-00-04  
Hanger Bolt M8 X100L



### Specifications

<b>Brand</b>	Yokota
<b>Airconsumption (l/s)</b>	4,3
<b>Weight (kg)</b>	2,10
<b>Capacity pin (mm)</b>	20
<b>Airconnection</b>	PT 1/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	195
<b>mm B</b>	82
<b>Stroke (mm)</b>	36 x 33
<b>Strokes per minute</b>	2700
<b>Hosediameter (mm)</b>	6,5
<b>Safety standard</b>	EN ISO 11148-4
<b>Vibration standard</b>	EN ISO 28927-9
<b>Vibration value (m/s<sup>2</sup>)</b>	8
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	95
<b>Sound power (dB(A))</b>	106
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981147908

