

AUTO-SHUT-OFF SCREWDRIVER RRI-SP50416

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- New body-design
- Reversible
- Revolving rear-exhaust, silenced
- ergonomic grip
- easily adjustable

Related products



AC30A-F03E-B
Modular FRL Unit



TW-0
Spring Balancer 0,5-1,5kg

Related accessories



61022-TH001
Tool Holder, diameter 42mm



00-4507
Torque Adjust Key RRI screwdriver



ATLUB
Air Tool Oil, 1 litre



510R-027
Side Handle



Specifications

| | |
|---|----------------------|
| Brand | RedRoosterIndustrial |
| Bolt capacity (mm) | 6 ~ 8 |
| RPM | 380 |
| Torque (Nm) | 9 ~ 16 |
| Airconsumption (l/s) | 13 |
| Weight (kg) | 1,5 |
| Hexagon | 1/4" |
| Airpress max. (MPa) | 0,63 |
| mm A | 245 |
| mm B | 16 |
| mm C | 179 |
| mm D | 42,7 |
| Hosediameter (mm) | 6,5 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 11148-6 |
| Vibration value (m/s ²) | <2,5 |
| Vibration uncertainty (m/s ²) | 0,1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 76 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981428243 |

