

CORDLESS IMPULSE TOOL W/ BATTERY

YZ-NP950E

YOKOTA YZ-NP battery impulse wrenches are powerful, very accurate and most important, have no kick-back. The very compact design offers great accessibility to the joint. Tightening bolts M10 with torque levels up to 65 Nm with very high speed and remarkably low reaction forces. The combination of adjustment of the relief valve and speed setting of the motor gives a great fit-for-purpose adaptation to the specific bolted joint. Pulse check function: By teaching the tool the impulse cycle as a reference point, the tool is able to give a warning message for upcoming maintenance needs.

Characteristics:

- With retention pin built-in in the square drive
- No kickback
- High speed fastening
- Hybrid technology
- DC drive brushless motor

Delivered with battery, but without charger.

Related accessories

- | | |
|---|-------------------------------------|
|  | BPL-1820 |
| | Battery for YS-E, YZ-N and YZ-T ser |
|  | 0446-1801-00-00 |
| | Hanger clip YOKOTA cordless wrench |
|  | 0446-0017-00-00 |
| | Hanger YOKOTA |
|  | 61022-TH005 |
| | Tool Holder |
|  | 0446-0029-00-01 |
| | Rubber protection cover Battery |
|  | 0457-0029-00-00 |
| | Rubber protection cover YZ-N950/A/Z |



Specifications

| | |
|---|----------------|
| Brand | Yokota |
| Square Drive | 3/8" |
| Bolt capacity (mm) | 8 - 10 |
| RPM | 2000 - 4800 |
| Torque (Nm) | 45 ~ 60 |
| Weight w/o battery (kg) | 1,25 |
| mm A | 164 |
| mm B | 29,5 |
| Battery voltage (Volt) | 18 |
| Battery type Li-ion....(Ah) | 2,0 |
| Safety standard | EN ISO 11148-6 |
| Vibration standard | EN ISO 28927-2 |
| Vibration value (m/s ²) | < 2,5 |
| Vibration uncertainty (m/s ²) | 1 |
| Sound standard | ISO 15744 |
| Sound pressure (dB(A)) | 79 |
| Sound uncertainty (dB(A)) | 3 |
| EAN | 8717981415434 |

