

# IMPULSE WRENCH 3/4 SHUT-OFF YLTX150

YOKOTA impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor and auto shut-off. No-lube airmotor.

## Related products



**AC30A-F03E-B**  
Modular FRL Unit



**TW-5C**  
Spring balancer 2,5-5,0 kg

## Related accessories



**ATLUB**  
Air Tool Oil, 1 litre



## Specifications

Brand	Yokota
Bolt capacity (mm)	16
RPM	4400
Torque (Nm)	140 - 210
Airconsumption (l/s)	11,8
Weight (kg)	2,95
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	237
mm B	38,5
Hosediameter (mm)	9,5
Square Drive / Hexagon	3/4"
Safety standard	EN ISO 11148-6
Air consumption no load (l/s)	17
Formal Capacity	140 - 210
Formal Serie From	0P0001
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	4,9
Vibration uncertainty (m/s <sup>2</sup> )	1
Sound standard	ISO 15744
Sound pressure (dB(A))	85,8
Sound power (dB(A))	96,8
Sound uncertainty (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	002
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981356553

