

# IMPULSE WRENCH 1/2" SHUT-OFF RRI-BIM65T

RED ROOSTER Cordless shut-off impulse wrench. High tightening speed combined with good accuracy. No reaction forces during the tightening process. Brushless motor for long motor life and high efficiency. No tightening functionality when battery charge is low, thus process safety improves. Very well suited in areas where cables and hoses impede handling flexibility of tools, such as interiors of cars, coaches and trains.

**Characteristics:**




- Brushless motor
- Lithium-Ion battery (choice for 2,5 Ah or 5,0 Ah capacity)
- LED status indicates: Reverse, OK, NG, Battery low
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Variable speed control with non-contact trigger
- Run-down speed: 3200 RPM

Battery and charger to be ordered separately

**Related products**

-  **BB200D-325**  
18V 2.5Ah Battery, Li-ion
-  **B74SC180B**  
Programmer
-  **BB200D-350**  
18V 5.0Ah Battery, Li-ion
-  **B84192B**  
18-20V Charger
-  **E86B-VD**  
Power Cord (EU)

**Related accessories**

-  **C16180C-40**  
Battery Protection Cover 18V 4.0 Ah
-  **C16180C-20**  
Battery Protection Cover 18V 2.0 Ah
-  **61022-TH005**  
Tool Holder
-  **B10PW15**  
Back Panel Cover (ALU)



**Specifications**

Brand	RedRoosterIndustrial
Square Drive	1/2"
Bolt capacity (mm)	8 - 10
RPM	3200
Torque (Nm)	45 - 65
Weight w/o battery (kg)	1,9
mm A	29
mm B	240
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,5 / 5,0
Vibration standard	EN ISO 28927-2
Vibration value (m/s <sup>2</sup> )	12,255
Vibration uncertainty (m/s <sup>2</sup> )	1,5
Sound standard	ISO 15744
Sound pressure (dB(A))	79,5
Sound uncertainty (dB(A))	3
EAN	8717981387090

