

# TAPPING MACHINE

## RRI-T330M12

The RED ROOSTER universal tapping machine RRI-T330M12 has been developed for manual thread tapping.

The direction of rotation is easily adjusted with the rocker switch.

It is an ergonomically developed tool that fits well in the hand.

Exhaust through grip, sound muffled.

Thanks to the quick-change holder, different sizes of tap holders can be changed quickly and easily.

Characteristics:

- Can be used both left and right handed.
- Side handle included for extra stability.
- Low air consumption.
- Low in vibrations.
- Can be used for M6 to M12 taps.

### Related products



**AC30A-F03E-B**  
Modular FRL Unit

### Related accessories



**775-0309**  
M6 Tap holder ISO



**775-0311**  
M12 Tap holder ISO



**775-0310**  
M8 Tap holder ISO



**775-0312**  
M10 Tap holder ISO



**ATLUB**  
Air Tool Oil, 1 litre



### Specifications

<b>Brand</b>	RedRoosterIndustrial
<b>RPM</b>	330
<b>Airconsumption (l/s)</b>	15
<b>Weight (kg)</b>	1,63
<b>Drill chuck</b>	B-12
<b>Capacity steel (mm)</b>	M6-M12
<b>Direction</b>	L+R
<b>Airconnection</b>	PT 1/4"
<b>Airpress max. (MPa)</b>	0,63
<b>mm A</b>	215
<b>mm B</b>	160
<b>mm C</b>	45
<b>Hosediameter (mm)</b>	10
<b>Power (kW)</b>	0,39
<b>Safety standard</b>	EN ISO 11148-3
<b>Vibration standard</b>	EN ISO 28927-5
<b>Vibration value (m/s<sup>2</sup>)</b>	0,3
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	0,1
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	86
<b>Sound power (dB(A))</b>	97
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981392728

