

# DIE GRINDER ANGLE 20000 RPM RRI-3506

RED ROOSTER die grinders are extremely suitable for de-burring applications as well as weld seam finishing and general die grinding applications.

**Characteristics:**

- \* The RRG range of die grinders are developed for enhanced productivity.
- \* The rubber cover allows the hand to grip the tool firmly due to the unique ergonomic design.
- \* The grinders have an adjustable rear exhaust.
- \* Air inlet with a swivel allowing the tool to be very flexible, especially in difficult access areas.
- \* When depressed fully the safety lever lays flat against the tool adding extra comfort for the operator.

**Related products**



**AC30A-F03E-B**  
Modular FRL Unit

**Related accessories**



**1001-0659-00-01**  
Adaptor 3mm for 6mm Chuck



**ATLUB**  
Air Tool Oil, 1 litre



**Specifications**

<b>Brand</b>	<b>RedRoosterIndustrial</b>
<b>RPM</b>	<b>20.000</b>
<b>Airconsumption (l/s)</b>	<b>4,9</b>
<b>Weight (kg)</b>	<b>0,55</b>
<b>Sound level (dB(A))</b>	<b>80</b>
<b>Airconnection</b>	<b>PT 1/4"</b>
<b>Airpress max. (MPa)</b>	<b>0,63</b>
<b>mm A</b>	<b>154</b>
<b>mm B</b>	<b>38</b>
<b>mm C</b>	<b>19</b>
<b>mm D</b>	<b>82</b>
<b>Hosediameter (mm)</b>	<b>6,5</b>
<b>Collet chuck (mm)</b>	<b>6</b>
<b>Power (kW)</b>	<b>0,22</b>
<b>Vibration level (m/s²)</b>	<b>1</b>
<b>Wheel size (mm)</b>	<b>40</b>
<b>Safety standard</b>	<b>EN ISO 11148-7</b>
<b>EAN</b>	<b>8717981033645</b>

