

# AUTO-SHUT-OFF SCREWDRIVER 0,8~3,0NM ATEX RRI-SL23003-EX

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used. ATEX classification: Ex II 2G IIB T4 / Ex II 2D IIIB T135°C.

### **Characteristics:**

- New straight body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

# **Related products**



AC30A-F03E-B Modular FRL Unit



**Spring Balancer Hosereel** 

### Related accessories



00-4507

HTB-0

**Torque Adjust Key RRI screwdriver** 



ATLUB

Air Tool Oil, 1 litre



# **Specifications**

| Brand                  | RedRoosterIndustrial   |
|------------------------|------------------------|
| Bolt capacity (mm)     | 4                      |
| RPM                    | 3000                   |
| Torque (Nm)            | 0,8 - 3,0              |
| Airconsumption (I/s)   | 11                     |
| Weight (kg)            | 0,87                   |
| Hexagon                | 1/4"                   |
| Airpress max. (MPa)    | 0,63                   |
| mm A                   | 269                    |
| mm B                   | 39                     |
| mm C                   | 16                     |
| mm D                   | 15                     |
| Hosediameter (mm)      | 6,5                    |
| Execution              | Straight - lever start |
| Vibration level (m/s²) | < 2,5                  |
| Safety standard        | EN ISO 11148-6         |
| EAN                    | 8717981460472          |

