

# HOIST/TROLLEY COMBINATION 6000 KG TMH-6000-LHR

Heavy duty hoist built into low headroom trolley frame with high efficiency motor gearbox

#### STANDARD FEATURES:

- TOKU rotary vane motor
- Failsafe automatic internal disc brake
- Trolley travel self braking
- Choice of pendant controls or control stations
- Upper & lower limit switches
- Forged alloy steel safety swivel hooks with safety catch
- Anti-tilt & anti-drop plates
- Wheel profile to suit parallel or tapered flanges

#### AVAILABLE OPTIONS:

- Marine specification paint systems
- ATEX Category 2 (zone 1/21) specification
- Chain collectors (PVC, galvanised or stainless steel)
- Travel limits
- Beam brake
- Articulated trolley for small beam radius

#### Related products



42-02-35-VRD

4-Button Pendant Valve Assy TCR/TMH



13X36RTS

Chain RTS EN 818-7



13X36

Chain EN 818-7



#### Specifications

Brand	RedRooster
Number of chain falls	2
Lowering speed full load (m/min)	5,1
Flange width with integrated hoist (mm)	110 - 300
Weight incl. 3m lift (kg)	300
Lifting speed full load (m/min)	2,7
Lifting speed 0-load (m/min)	5,4
Chain weight (kg/m)	3,8
Chain (mm)	13x36
Airconnection	PT 1"
Workingpressure (MPa)	0,4 - 0,63
Capacity (kg)	6000
Air consumption lifting (l/s)	56
Standard travel speed (m/min)	6
Air consumption traveling (l/s)	25
EAN	8717981380305