

AIR CHAIN HOIST 15000 KG TMH-15000P5E

The NEW RED ROOSTER TMH series air chain hoists has the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely durable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a full load supporting eye for installation and securing the hoist (during lifting operation) for extra safety.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (80 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

Related products



42-02-28-VRD

Pendant Valve Assy TCR/TMH



13X36RTS

Chain RTS EN 818-7



13X36

Chain EN 818-7



Specifications

Brand	RedRooster
Airconsumption (l/s)	58,3
Number of chain falls	5
Lowering speed full load (m/min)	2,04
Weight incl. 3m lift (kg)	280
Lifting speed full load (m/min)	1,08
Lifting speed 0-load (m/min)	2,16
Airconnection	1" PT
Airpress max. (MPa)	0,63
mm A	855
mm B	466
mm C	152,5
mm D	313,5
mm E	52
mm F	300
mm G	275
mm H	67
mm I	84
mm J	58
mm K	75
Hosediameter (mm)	19
Capacity (kg)	15000
Airconnection exhaust	1"
EAN	8717981340576

