YOKOTA

CONTROLLED PRECISION IN TIGHTENING

DOWEL PIN PULLER
YDP-13

The Yokota dowel pin puller is used in matrix, casting and press-moulding industries, for setting and removing dowel pins in moulds or presses. The dowel pin puller is an easily operated air tool and can simplify the pulling or hammering operation
of the threaded dowel pins, saving time and improving working efficiency.
Delivered including:
M6 x 50L: 6502-0022-00-09,
M5 x 50L: 6502-0022-00-13 and
M4 x 50L: 6502-0022-00-17.



Related accessories

- 6502-0022-00-07 Hanger Bolt M8X150L
- 6502-0022-00-08 Hanger Bolt M8X200L
- 6502-0022-00-06 Hanger Bolt M8X100L
- 6502-0022-00-12 Hanger Bolt M6X200L
- 6502-0022-00-14 Hanger Bolt M5X100L
- 6502-0022-00-10 Hanger Bolt M6X100L
- 6502-0022-00-19 Hanger Bolt M4X150L
- 6502-0022-00-11 Hanger Bolt M6X150L
- 6502-0022-00-13 Hanger Bolt M5X 50L
- 6502-0022-00-17 Hanger Bolt M4X 50L
- 6502-0022-00-18 Hanger Bolt M4X100L
- 6502-0022-00-09 Hanger Bolt M6X 50L
- 6502-0022-00-16 Hanger Bolt M5X200L
- 6502-0022-00-20 Hanger Bolt M4X200L
- 6502-0022-00-15 Hanger Bolt M5X150L

Specifications

Brand	Yokota
Airconsumption (l/s)	3,3
Weight (kg)	1,35
Capacity pin (mm)	13
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	162
mm B	75
Stroke (mm)	30 x 25
Strokes per minute	5000
Hosediameter (mm)	6,5
Vibration standard	EN ISO 28927-9
Vibration value (m/s²)	5,1
Vibration uncertainty (m/s²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981141418

