TOKU

MAKING THE RIGHT IMPACT

ANGLE GRINDER 125MMX22MM TAG-50MLH

This angled grinder by Toku is used for grinding and cutting. The dead-handle is vibration reduced. The grinder has an integrated speed-setting regulator for maximum safety and optimal speed for best material removal
Characteristics:
*** Ergonomic design, well balanced**
*** Compact and lightweight**
*** For cutting and grinding purposes**
*** Exhaust silenced**
*** Low vibrationlevel**
*** M14 Spindle**

Related accessories



2400-046-11
Dead Handle Vibration Red.

13-40-04-014
Combi Spanner 14x19

13-08-02-147
Socket Bar



QN-M14
Quick Nut M14X2.0P

9310-3004-00-00
Rubber pad G-50



ATLUB
Air Tool Oil, 1 litre

42-05-80-H00
Wheel Ring



Specifications

Brand	**Toku**
RPM	**12000**
Airconsumption (l/s)	**10,8**
Weight (kg)	**2,02**
Airconnection	**PT 3/8"**
Airpress max. (MPa)	**0,63**
mm A	**267**
mm B	**85**
mm C	**33**
mm D	**50**
Hosediameter (mm)	**10**
Spindle	**M14 x 2**
Power (kW)	**0,67**
Wheel size (mm)	**125 x (0,8 - 7) x 22,2**
Vibration standard	**EN ISO 28927-1**
Vibration value (m/s²)	**12,4**
Vibration uncertainty (m/s²)	**4,10**
Sound standard	**ISO 15744**
Sound pressure (dB(A))	**89**
Sound power (dB(A))	**100**
Sound uncertainty (dB(A))	**3**
EAN	**8717981000616**

