

COMPOSITE IMPACT WRENCH 3/4 RRI-2500M

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-2500M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use.
Breakloose torque: 2.700 Nm.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- Power adjustable, 2 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown

Related products

-  DO605421001
Impact Socket Set 3/4" deep 10-parts
-  DO605401001
Impact Socket Set 3/4" 10-parts

Related accessories

-  DOESR-2
Ret Ring
-  ATLUB
Air Tool Oil, 1 litre
-  DOESR-1
Ret Ring



Specifications

Brand	RedRoosterIndustrial
Square Drive	3/4"
Version	R+H
Bolt capacity (mm)	24
Impact mechanism	Mechoneer
RPM	5500
Torque (Nm)	2000
Force adjustment	L/R 2 Pos.
Airconsumption (l/s)	16
Weight (kg)	3,5
Airconnection	3/8"
Airpress max. (MPa)	0,63
mm A	187
mm B	45
Hosediameter (mm)	13
Max. breakaway torque (Nm)	2700
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	7
Vibration uncertainty (m/s ²)	1,19
Sound standard	ISO 15744
Sound pressure (dB(A))	88,4
Sound power (dB(A))	99,4
Sound uncertainty (dB(A))	3
EAN	8717981400805

