

# IMPACT WRENCH 1" MI-4500ELR

This industrial impact wrench by Toku has proven capabilities. The MI-4500ELR is developed for tightening and untightening applications. The closed hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is suitable for the heaviest use in the industry.

**Characteristics:**

- \* Ergonomic design, well balanced
- \* Compact
- \* Power adjustable, 4 positions
- \* Long anvil

**Related products**



**D00100-1-007**  
 Impact Socket Set Long 1" 7-parts

**Related accessories**



**ATLUB**  
 Air Tool Oil, 1 litre



**DOESR-3**  
 Ret Ring



**Specifications**

<b>Brand</b>	Toku
<b>Square Drive</b>	1"
<b>Version</b>	R+H
<b>Bolt capacity (mm)</b>	45
<b>Impact mechanism</b>	Gesloten Hamer
<b>RPM</b>	3700
<b>Torque (Nm)</b>	2900
<b>Force adjustment</b>	R/L 4 Standen
<b>Airconsumption (l/s)</b>	23
<b>Weight (kg)</b>	14,5
<b>Airconnection</b>	PT 1/2"
<b>Airpress max. (MPa)</b>	0,63
<b>mm B</b>	60
<b>Hosediameter (mm)</b>	13
<b>mm A*</b>	584
<b>Max. breakaway torque (Nm)</b>	3470
<b>Vibration standard</b>	EN ISO 28927-2
<b>Vibration value (m/s<sup>2</sup>)</b>	11,3
<b>Vibration uncertainty (m/s<sup>2</sup>)</b>	1,62
<b>Sound standard</b>	ISO 15744
<b>Sound pressure (dB(A))</b>	95
<b>Sound power (dB(A))</b>	106
<b>Sound uncertainty (dB(A))</b>	3
<b>EAN</b>	8717981148332

