RED ROOSTER
LEADING IN POWER TOOL SOLUTIONS

AIR CHAIN HOIST 3000 KG
TMH-3000LFPE

The new RED ROOSTER LF series of lubrication free hoists is the latest addition in a line of new models within the Red Rooster air hoist range. The oil free operation allows the hoist to run whilst preventing any oil being exhausted into the atmosphere, making the units ideal for use where a clean environment is a requirement. These new air hoists are suitable for food, chemical, pharmaceutical and painting industries.

CHARATERISTICS:
- Precise variable speed control
- Optimum control of the load
- Robust and reliable
- Mechanical end stop
- High quality RUD hoist chain
- Full load supporting eye for safe installation
- Standard delivered including ATEX zone 2 certificate


OPTIONS:
- Paint systems for C5 Marine
- Zone 1 ATEX certification
- Chain collectors
- Hook or clevis options
- Air supply systems and valves

Related products


42-02-28-VRD
Pendant Valve Assy TCR/TMH


13X36
Chain EN 818-7


AW60-F10DE-D
Modular Type Filter Regulator



Specifications

Brand	RedRooster
Number of chain falls	1
Lowering speed full load (m/min)	5,7
Lowering speed 0-load (m/min)	3,1
Weight incl. 3m lift (kg)	99
Lifting speed full load (m/min)	3,1
Lifting speed 0-load (m/min)	6,4
Chain weight (kg/m)	3,8
Chain (mm)	13 x 36
Airconnection	1"BSPT
Airconsumption fullload (l/s)	51
mm A	537
mm B	314
mm C	189
mm D	125
mm E	265
mm F	311
mm H	50
mm I	34
Hosediameter (mm)	19
Workingpressure (MPa)	0,4 - 0,63
Capacity (kg)	3000
Airconnection exhaust	1"
EAN	8717981389308