

AIR CHAIN HOIST 3000 KG TMH-3000PE

The NEW RED ROOSTER TMH series air chain hoists has the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a full load supporting eye for installation and securing (during lift applications) the hoist for extra safety.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (80 dBA)
- Working air pressure 0,4 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

Related products



42-02-28-VRD

Pendant Valve Assy TCR/TMH



13X36RTS

Chain RTS EN 818-7



AC60-F10DM-8-B

FrI Unit 13X36



Chain EN 818-7



Specifications

Brand	RedRooster
Number of chain falls	1
Lowering speed full load (m/min)	10,5
Lowering speed 0-load (m/min)	6,4
Weight incl. 3m lift (kg)	99
Lifting speed full load (m/min)	5,4
Lifting speed 0-load (m/min)	10,7
Chain weight (kg/m)	3,8
Chain (mm)	13 x 36
Chainbag/Chainbucket	+
Loadlimiter	+
Airconnection	1"BSPT
Airpress max. (MPa)	0,63
Airconsumption fullload (I/s)	58,3
mm A	537
mm B	190
mm C	125
mm D	265
mm E	315
mm F	50
mm G	34
mm H	35
mm I	45
Hosediameter (mm)	19
Capacity (kg)	3000
Airconnection exhaust	1"
EAN	871798134049

