

IMPACT WRENCH 3/4 MI-20PGL

This Toku Impact Wrench has an excellent weight/power ratio. The MI-20PL is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use. Execution with extended anvil

Characteristics:

- Ergonomic design, well balanced
- Compact and durable
- Clutch: Twin Hammer
- Adjustable power, 4 positions
- Exhaust through grip, with silencer

Related products



DO605421001

Impact Socket Set 3/4" deep 10-parts



AC40A-F04-D

Modular FRL unit



DO605401001

Impact Socket Set 3/4" 10-parts

Related accessories



DOESR-2

Ret Ring



ATLUB

Air Tool Oil, 1 litre



DOESR-1

Ret Ring



Specifications

Brand	Toku
Square Drive	3/4"
Version	R+H
Bolt capacity (mm)	24
Impact mechanism	Twin-Hammer
RPM	5000
Torque (Nm)	1000
Force adjustment	R/L 4
Airconsumption (l/s)	15
Weight (kg)	4,0
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	335
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	2400
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	8,5
Vibration uncertainty (m/s ²)	1,34
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981380909

