

DRILL 6-8 MM 2800 RPM

YRD-6NBK

This Yokota drill is suitable for industrial applications. The two-step trigger allows easy setting of the drill tip at first stage, and afterward high rpm for maximum drilling-speed.

Characteristics:

- * Compact and lightweight
- * Low vibration level
- * Exhaust through grip, with silencer
- * Ergonomic design
- * Includes 10 mm key-less drill chuck

Related products



AC30A-F03E-B
Modular FRL Unit

Related accessories

BHS-10MM

Drill Chuck (Quick Change) 3/8X24Nf



ATLUB
Air Tool Oil, 1 litre



Specifications

Brand	Yokota
RPM	2800
Airconsumption (l/s)	8,3
Weight (kg)	0,90
Drill chuck	3/8" x 24UNF
Capacity steel (mm)	6 - 8
Direction	R
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	151
mm B	140
mm C	21
Hosediameter (mm)	10
Power (kW)	0,33
Safety standard	EN ISO 11148-3
Vibration standard	EN ISO 28927-5
Vibration value (m/s ²)	< 2,5
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	77
Sound uncertainty (dB(A))	3
EAN	8717981000678

